

figure.conf

```
#####  
# Lines beginning with # are comments and ignored.  
##  
rpcuser=introduce any name of rpcuser as you want, for example, viggo  
rpcpassword=introduce any password as you want, for example, x  
rpcallowip=127.0.0.1  
rpcport=12454  
port=8677  
listen=1  
server=1  
daemon=1  
gen=0  
genproclimit=-1  
maxconnections=500  
addnode=188.225.75.13:8677  
addnode=188.225.75.6:8677  
addnode=188.225.75.9:8677  
addnode=188.225.75.12:8677  
addnode=188.225.75.11:8677  
addnode=188.225.76.249:8677  
addnode=112.165.82.230:8677  
addnode=160.16.217.204:8677  
addnode=18.191.129.226:37846  
addnode=18.219.27.44:8677  
addnode=188.225.77.191:8677  
addnode=202.39.49.57:8677  
addnode=212.12.20.198:50368  
addnode=31.187.71.102:8677  
addnode=31.187.71.28:57150  
addnode=45.76.17.37:8677  
addnode=52.14.168.126:48216  
addnode=[2001:41d0:a:4aa8::]:8677  
addnode=112.165.82.230:8677  
addnode=160.16.217.204:8677  
addnode=18.219.27.44:8677  
addnode=167.114.169.209:8677  
#####
```