

bulwark.conf

```
*****
rpcuser=introduce any name of rpcuser as you want, for example, viggo
rpcpassword=introduce any password as you want, for example, x
rpcallowip=127.0.0.1
rpcport=52541
port=52543
#(0=off, 1=on) daemon - run in the background as a daemon and accept commands
daemon=1
#(0=off, 1=on) server - accept command line and JSON-RPC commands
server=1
listen=1
gen=0
genproclimit=-1
maxconnections=500
addnode=62.77.157.94:52543
addnode=45.76.88.217:52543
addnode=149.28.240.22:52543
addnode=45.77.126.106:52543
addnode=144.202.11.154:52543
addnode=195.201.160.201:52543
addnode=107.175.56.135:52543
addnode=46.101.145.229:52543
addnode=93.115.96.135:52543
addnode=76.74.178.212:52543
addnode=45.63.49.239:52543
addnode=45.32.102.162:52543
addnode=91.223.223.248:52543
addnode=89.40.15.57:52543
addnode=207.148.15.84:52543
addnode=173.212.197.59:52543
addnode=198.13.39.76:52543
addnode=199.247.22.56:52543
addnode=167.114.152.194:52543
addnode=207.246.126.171:52543
addnode=173.255.245.5:52543
addnode=140.82.7.108:52543
addnode=95.179.131.149:52543
addnode=167.99.166.224:52543
addnode=188.166.144.239:52543
addnode=206.81.1.46:52543
addnode=104.156.226.83:52543
addnode=104.207.158.163:52543
addnode=107.181.166.174:52543
addnode=51.255.173.170:52543
addnode=108.61.215.101:52543
addnode=31.24.227.197:52543
*****
```