

dyno.conf

```
#####  
# Lines beginning with # are comments and ignored.  
##  
rpcuser=introduce any name of rpcuser as you want, for example, viggo  
rpcpassword=introduce any password as you want, for example, x  
rpcallowip=127.0.0.1  
rpcport=29998  
port=40822  
#(0=off, 1=on) daemon - run in the background as a daemon and accept commands  
daemon=1  
#(0=off, 1=on) server - accept command line and JSON-RPC commands  
server=1  
listen=1  
gen=0  
genproclimit=-1  
maxconnections=120  
addnode=173.249.40.246:40822  
addnode=176.223.128.103:40822  
addnode=194.182.87.71:40822  
addnode=209.250.232.127:40822  
addnode=31.220.49.137:40822  
addnode=35.231.143.86:40822  
addnode=112.216.30.90:40822  
addnode=207.148.74.173:40822  
addnode=45.76.206.193:40822  
addnode=109.167.143.142:40822  
addnode=45.32.106.30:40822  
addnode=37.221.193.194:40822  
addnode=121.158.205.187:40822  
addnode=178.208.255.16:40822  
addnode=209.250.232.127:40822  
addnode=212.237.35.148:40822  
addnode=35.231.143.86:40822  
addnode=87.229.103.131:40822  
addnode=[2002:c385:91a5::c385:91a5]:40822  
addnode=209.250.232.127:40822  
addnode=194.87.103.119:40822  
addnode=144.202.66.39:40822  
addnode=212.237.33.202:40822  
addnode=109.167.143.142:40822  
addnode=111.231.140.76:40822  
addnode=144.202.75.121:40822  
addnode=173.249.44.68:40822  
#####
```

dyno.conf